

# GENERAL SPECIFICATIONS

HT 10400-S

	Material	Body	304 grade stainless steel (opt. 316 grade).	
		Arm	304 grade stainless steel (opt. 316 grade).	
	Available for	INDOOR/OUTDOOR <input checked="" type="checkbox"/>		INDOOR <input type="checkbox"/>
	Energy	110/220-240V 50-60Hz. AC (±%10) - 24V DC		
	Control System	Dry contact (ground control)		
	Nr. of Passage Lanes	<b>Double Unit</b>		<b>Single Unit</b>
			<input type="checkbox"/>	
				<input checked="" type="checkbox"/>
	Rotor System	<b>90° (4 Arms) Rotor System</b>		<b>120° (3 Arms) Rotor System</b>
			<input checked="" type="checkbox"/>	
				<input type="checkbox"/>
	Operation	BI-DIRECTIONAL <input checked="" type="checkbox"/>		UNI-DIRECTIONAL <input type="checkbox"/>
	Indicators		STANDARD <input checked="" type="checkbox"/>	OPTIONAL <input type="checkbox"/>
			STANDARD <input type="checkbox"/>	OPTIONAL <input type="checkbox"/>
	Emergency	Arms allow free passage		
	Reduced Mobility (ADA) Compatibility	AVAILABLE <input type="checkbox"/>		NOT AVAILABLE <input checked="" type="checkbox"/>

For further details, please download "Technical Specifications" file.